

**DATASHEET 5.3**

# SO-QSFP-IR4-PSM

**QSFP+, 40G Ethernet IR4, SM, 1310nm, 2km, 7.4dB, MPO (APC)**

## OVERVIEW

The SO-QSFP-IR4-PSM is a QSFP+ (Quad Small Form-factor Pluggable Plus) transceiver for 40Gbps applications such as inter- and intra-connect within and between data centers between switches, routers, storage equipment etc.

The SO-QSFP-IR4-PSM converts 4x 10Gbps flows into four channels at 1310nm up to 2 km over a SingleMode (SM) fiber.

The transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

The SO-QSFP-IR4-PSM provides transport over an MPO/MTP12 or 8 ribbon fiber cable.

## TECHNICAL DATA

Parameter	Value
Technology	Grey QSFP+
Transmission media	SM (1x MPO)
Typical reach	2km
Nominal wavelength	1310nm
Interface standards	40GBASE-IR4
Bit rate support	41.25 Gbps <sup>1</sup> 10.3125 Gbps <sup>2</sup>
Protocol support	40GbE
Power budget	0 – 7.4dB
Power consumption	< 3.5W
Operating temperature	0°C to +70°C
Storage temperature	-40°C to +85°C

Parameter	Value
<b>Transmitter data:</b>	
Output power, total	Min: -5.2dBm <sup>3</sup> Max: +0.5dBm <sup>3</sup>
Transmit wavelength	11260 – 1360nm nm
<b>Receiver data:</b>	
Minimum input power	-12.6Bm <sup>2 3 4</sup>
Overload (max power)	+2.4dBm <sup>2 3 4</sup>
Wavelength range	1260 – 1360nm
LOS Assert	Min -30dBm
LOS De-Assert	Max -15dBm
LOS Hysteresis	Min 0.5dB
DDM	Yes
MSA compliance	QSFP+ MSA

<sup>1</sup> Aggregated line rate

<sup>2</sup> Per channel

<sup>3</sup> Average power,

<sup>4</sup> Measured with PRBS 231-1 test pattern, 10.3125Gb/s, BER<10<sup>-12</sup>


### Safety / regulatory compliance

TUV/UL/FDA (contact Smartoptics for latest certification information)  
RoHS compliance

MPO (Multi-fiber Push On) is an optical connector for ribbon cables with four to twenty-four fibers.

MTP is a specific brand of an MPO connector.

Note: An MPO/MTP connector with 8-degree Angled Physical Contact (APC) shall be used with this product to minimize MPO/MTP connection induced reflections.



## ORDERING INFORMATION

Ordering number	Description
SO-QSFP-IR4-PSM	QSFP+, 40G Ethernet IR4, SM, 1310nm, 2km, 7.4dB, MPO (APC)

## GENERAL DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable (DAC). Electrical or optical cable with attached connectors..
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range:	Max operating case temperature range. Commercial temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption. Will vary over temperature.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$ .
Receiver max input power:	Maximum average input power giving a BER, normally $1E^{-12}$ .
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.