

DATASHEET 5.3

# SO-QSFP-LR4-PSM

**QSFP+, 40G Ethernet LR4, SM, 1271/1291/1311/1331nm, 20km, 10.2dB, LC**

## OVERVIEW

The SO-QSFP-LR4-PSM is a QSFP+ (Quad Small Form-factor Pluggable Plus) transceiver for 40 Gbps applications where the transport is made using four channels at 10 Gbps. It is intended for use in inter- and intra-connect applications within and between data centers with switches, routers, storage equipment etc. The transceiver can also be used for 10GbE-LAN interconnect applications, providing a higher density as compared to four individual 10G connections using e.g. SFP+ transceivers.

The SO-QSFP-LR4-PSM provides transport over an MPO/MTP 12 or 8 ribbon fiber cable up to 10 km over a SingleMode (SM) fiber.

## TECHNICAL DATA

Parameter	Value
Technology	Grey QSFP+
Transmission media	SM (1x MPO/APC)
Typical reach	10km
Nominal wavelengths	1310nm
Interface standards	40GBASE-LR4
Bit rate support	41.25 Gbps <sup>1</sup> 4x 10.3125Gbps <sup>2</sup>
Protocol support	40GbE / 4x 10GbE-LAN Infiniband QDR, DDR, SDR
Power budget	0 – 6.6dB
Power consumption	< 3.5W
Operating temperature	0°C to +70°C
Storage temperature	-40°C to +85°C

Parameter	Value
<b>Transmitter data:</b>	
Output power, per lane	Min: -6.0dBm <sup>3</sup> Max: +1.5dBm <sup>3</sup>
Transmit wavelength	1260 – 1355nm
<b>Receiver data:</b>	
Minimum input power	-12.6Bm <sup>2 3 4</sup>
Overload (max power)	+2.3dBm <sup>2 3 4</sup>
Wavelength range	1260 – 1355nm
LOS Assert	Min -30dBm
LOS De-Assert	Max -15dBm
LOS Hysteresis	Min 0.5dB
DDM	Yes
MSA compliance	QSFP+ MSA, SFF-8436

<sup>1</sup> Aggregated line rate

<sup>2</sup> Per lane

<sup>3</sup> Average power,

<sup>4</sup> At BER less than 10<sup>-12</sup>, with a 231-1 PRBS

### Safety / regulatory compliance

TUV/UL/FDA (contact Smartoptics for latest certification information)  
RoHS compliance

## ORDERING INFORMATION

Ordering number	Description
SO-QSFP-LR4-PSM	QSFP+, 40G Ethernet LR4, SM, 1310nm, 10km, 6.6dB, MPO (APC)

## GENERAL DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable (DAC). Electrical or optical cable with attached connectors..
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range:	Max operating case temperature range. Commercial temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption. Will vary over temperature.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$ .
Receiver max input power:	Maximum average input power giving a BER, normally $1E^{-12}$ .
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.