

DATASHEET 5.0

SO-XFP-ER-DXXXX

XFP, 10G Multirate, DWDM, 100GHz, DDM, 14dB, 40km, D9180-D9610 (44ch)

OVERVIEW

The SO-XFP-ER-Dxxxx is a versatile DWDM transceiver supporting a wide range of traffic formats ranging from 9.95 to 11.1 Gbps. The transceiver is provided in 44 channel versions at the 100GHz DWDM grid as specified in the ITU-T 694.1 standard.

The distance performance is in accordance with the IEEE 802.3ae ER/EW-standard, providing a bridgeable distance of up to 40km for 10GbE-LAN (10GBASE-ER) and 10GbE-WAN (10GBASE-EW) services.

This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

TECHNICAL DATA

Technology	DWDM 100GHz XFP	
Transmission Media	SM (2x LC)	
Typical reach	40 km	
Nominal wavelength	191.80 - 196.10 THz (44ch)	
Interface standards	10GBASE-ER 10GBASE-EW 1200-SM-LL-L 10G FC OC-192 IR-2, IR-3 STM S-64.2b, S-64.3b	
Bit rate range	9.95 - 11.1 Gbps	
Protocols	Eth:	10GbE-LAN, 10GbE-WAN
	OTN:	OTU2e, OTU2
	SDH/SONET:	STM-64/OC-192
	FC:	10G FC
	CPRI:	Opt 8 (10.1376 Gbps)
Power budget	0.0 - 14.0 dB	
Dispersion tolerance	800 ps/nm ¹⁾	
Power consumption	< 2.0W	
Transmitter data	Output power:	Min: -1.0 dBm Max: +4.0 dBm
	Tx wavelength:	191.80 - 196.10 THz in 100GHz steps (G.694.1)

Receiver data	Minimum input power:	-15.0 dBm ¹⁾
	Overload (max power):	+0.5 dBm
	Wavelength range:	1270 – 1600 nm
DDM	Yes	
MSA compliance	SFF-8431 SFF-8432 SFF-8472	

¹⁾@ 10.3Gbps

Regulatory Compliance

EMC / CE	EN 55022:2010
	EN 55024:2010
UL/Safety FCC	UL 60950-1
	47 CFR PART 15 OCT, 2013
RoHS	RoHS 6
	EN 60950-1:2006+A11+A1+A12+A2
	EN 60825-1:2014 EN 60825-2:2004+A1+A2

Storage temp.	-40°C to +85°C
----------------------	----------------

Note! See "Definitions" below.

ORDERING INFORMATION

Part number	Description
SO-XFP-ER-DXXXX	XFP, 10G Multirate, DWDM, 100GHz, DDM, 14dB, 40km, D9180-D9610 (44ch)

DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical or optical cable with attached connectors.
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than $1E^{-12}$. Defined at a specific bit rate.
Temperature range:	Max operating case temperature range. Standard temperature range: Typically 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): Typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$.
Receiver max input power:	Maximum average input power at specified BER, normally $1E^{-12}$.
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.