

DATASHEET 5.0

SO-XFP-LR20

XFP, 10G Multirate, 1310nm, SM, DDM, 12dB, 20km

OVERVIEW

The SO-XFP-LR20 is a versatile 1310nm transceiver for SingleMode fiber supporting a wide range of traffic formats. The optical performance exceeds the IEEE 802.3ae LR/LW-standard, providing a bridgeable distance of up to 20km for 10GbE-LAN (10GBASE-LR) and 10GbE-WAN (10GBASE-LW) services. It is also in compliance with SDH/SONET as well as Fiberchannel interface standards.

This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

TECHNICAL DATA

Technology	Grey XFP
Transmission Media	SM (2x LC)
Typical reach	20 km
Nominal wavelength	1310 nm
Interface standards	10GBASE-LR 10GBASE-LW OC-192 LR-1 STM I-64.1 10GFC 1200-SM-LL-L
Bit rate range	9.95 - 11.1 Gbps
Protocols	Eth: 10GbE-LAN 10GbE-WAN
	OTN: OTU2e OTU2
	SDH/SONET: STM-64/OC-192
	FC: 10G FC
	CPRI: Opt 8 (10.1376 Gbps)
Power budget	0.5 – 12.0 dB
Dispersion tolerance	0 C to +70 C

Power consumption	< 2.5W
Transmitter data	Output power: Min: -3.0 dBm Max: +1.0 dBm
	Tx wavelength: Min: 1290 nm Max: 1330 nm
Receiver data	Minimum input power: -15.0 dBm ¹⁾
	Overload (max power): +0.5 dBm
	Wavelength range: 1270 - 1600 nm
DDM	Yes
MSA compliance	SFF-8431
	SFF-8432
	SFF-8472

¹⁾@ 10.3Gbps

Regulatory Compliance

EMC / CE	EN 55022:2010 EN 55024:2010
UL/Safety FCC	UL 60950-1 47 CFR PART 15 OCT, 2013
RoHS	RoHS 6
TUV	EN 60950-1:2006+A11+A1+A12+A2 EN 60825-1:2014 EN 60825-2:2004+A1+A2

Storage temp.	-40°C to +85°C
----------------------	----------------

Note! See "Definitions" below.

ORDERING INFORMATION

Part number	Description
SO-XFP-LR20	XFP, 10G Multirate, 1310nm, SM, DDM, 12dB, 20km

DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical or optical cable with attached connectors.
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than 1E-12. Defined at a specific bit rate.
Temperature range:	Max operating case temperature range. Standard temperature range: Typically 0 C to +70 C (32 F to +158 F) Extended temperature range (E-temp): Typically -20 C to +75 C (-4 F to +167 F) Industrial temperature range (I-temp): -40 C to +85 C (-40 F to +185 F)
Power consumption:	Worst case power consumption.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally 1E ⁻¹² .
Receiver max input power:	Maximum average input power at specified BER, normally 1E ⁻¹² .
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.