



DATASHEET 4.4

DCP-M40-PAM4-ER+

Multi-format 40 channel DWDM open line system (20-60 km)




AN OPEN LINE PLATFORM DESIGNED FOR DCI

DCP-M is a true open line DWDM platform designed specifically for modern DCI. DCP-M has the form factor and usability of a passive multiplexer, but unlike a passive multiplexer it monitors the traffic, amplifies the signals for longer distances and can handle higher data rate protocols. DCP-M provides everything required for an open line system and is simple, reliable and open for all DCI protocol types. DCP-M offers an unparalleled level of plug and play simplicity regardless of traffic type and network application. The DCP-M family comprises four models for either 8 or 40 channels, dedicated for either 100G DWDM PAM4 traffic or for applications with any mix of PAM4, NRZ and coherent 100/400G channels.

DCP-M40-PAM4-ER+ IN SHORT

- 40 channel active DWDM multiplexer for open line systems
- Accepts any DWDM signal format: PAM4 (40G/100G), NRZ(1-32G), Coherent (QPSK/8QAM/16QAM)
- Extended reach (20-60 km)
- Unprecedented level of cost efficiency and ROI for 100G Data Center Interconnect (DCI)
- High speed multi-protocol capability
- Industry defining 1U form factor
- Automated configuration and zero touch provisioning - behaves like a passive multiplexer
- Automatic fiber distance measurement and dispersion compensation
- Modern REST based management architecture with standard and customizable APIs



AUTOMATED CONFIGURATION, ZERO-TOUCH PROVISIONING AND SMART MANAGEMENT

DCP-M brings an unprecedented level of plug and play simplicity to DWDM DCI networking, being designed with ease of use in mind. Power levels are automatically regulated and a visual confirmation via LEDs shows that channel and line are set up correctly. Automated configuration and zero-touch provisioning mean that installation and adding new connections can be done in minutes also by staff with only a basic knowledge of optical networking.

ORDERING INFORMATION

DCP-M Series product codes

DCP-M40-PAM4-ER+/HW	Base HW, 40 channel DWDM OLS, D921-D960, OSC, 20-55km, PAM4, NRZ, Coherent
DCP-M-ENL-7.x_SW	DCP-M Embedded Node Licence for software release 7.x
DCP-2-PSU-AC-FB	AC power supply for DCP platform, Front-to-Back airflow
DCP-2-PSU-DC-FB	DC power supply for DCP platform, Front-to-Back airflow

Spares

DCP-2-FAN-FB	Spare fan unit, Front-to-Back
--------------	-------------------------------

TECHNICAL SPECIFICATIONS

PRODUCT CONFIGURATION 40 channel DWDM Open Line System for metro DWDM, DCI and dark fiber connectivity.

Supported encodings:

- PAM4 (40G/100G)
- NRZ (1-32G)
- Coherent (QPSK/8QAM/16QAM)

Supported protocols:

- 1/10/40/100/200/400G Ethernet
- 1/2/4/8/16/32G Fiber Channel
- Other protocols may be supported, contact Smartoptics for more information.

FRONT SIDE CONNECTIONS All ports are of LC connector type

40 x DWDM client channels D921 to D960
1 x Line input/output port

VISUAL INDICATORS Status LED Power & Alarm status
Client LED: 40 x individual client Tx/Rx
Line LED: Line Tx/Rx

REAR SIDE CONNECTIONS	<p>Management and console ports 4 x RJ45 Management ports 10/100/1000 Base-T 1 x SFP Management port 1000 Base-X 1 x RS-232 serial port 1 x RJ-45 Local craft 10/100/1000 Base-T</p> <p>2 x Power supplies: Single/dual feeding. Hot swappable. 1 x Fan unit: Redundant plugin. Hot swappable.</p>
MANAGEMENT	<p>CLI, SSH, SNMPv2c, SNMPv3 NTP, SFTP, Syslog, RADIUS, TACACS+</p>
SOFTWARE UPGRADES	Traffic hitless software upgrades
DIMENSIONS	<p>Size (WxDxH) 440mm x 510mm x 1RU 17.3" x 20" x 1RU Weight: 13 Kg / 28.7 lbs.</p>
EYE SAFETY	Laser safety class 1M
POWER CONSUMPTION	<p>Typical consumption at 220VAC: Normal operation: 45W Max during power up: 65W</p> <p>AC Fuse: 100-127 VAC (3A) 200-240 VAC (1.5A)</p> <p>DC Fuse: -40 to -72 VDC (7A)</p>
ENVIRONMENTAL	<p>Operating temp: 0°C to +45°C Cooling: Front to back Humidity: 5% to 85% Altitude: 3000 m (10.000 ft)</p>
OPTICAL SPECIFICATION	<p>Fiber distance: 20 – 55 km Fiber link loss: 0 – 14 dB Fiber types: G.652 (SMF-28)</p>

NOTE. THE INFORMATION IN THIS DOCUMENT IS VALID FROM RELEASE R8.1.1